

Tire Direct
La nueva generación



Bvd. Campestre No. 72
Col. Casa Blanca, León, Gto.
C.P. 37170



+52 (477) 718.09.21
01800 000TIRE (8473)



info@tiredirect.com.mx
www.tiredirect.com.mx



Tire Direct



Tire Direct

LA NUEVA IMAGEN DE TURNPIKE FTG



TO START BUSINESS

LLANTA CERTIFICADA EN:

FTG


FUTURE TECHNOLOGY GENERATION

DISRUPCIÓN - CALIDAD - INNOVACIÓN

Tire Direct
La nueva generación


FTG
 FUTURE TECHNOLOGY GENERATION

Tire Direct

La nueva generación
FTG
 FUTURE TECHNOLOGY GENERATION


DS968

DD909

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	14PR	144	142	M	8.25	7.50,8.25	2800	2650	720	720	1054	279	15
11R22.5	16PR	146	143	M	8.25	7.50,8.25	3000	2725	830	830	1054	279	15
11R24.5	14PR	146	143	M	8.25	7.50,8.25	3000	2725	720	720	1104	279	15
11R24.5	16PR	149	146	M	8.25	7.50,8.25	3250	3000	830	830	1104	279	15
295/75R22.5	14PR	144	141	M	9.00	8.25,9.00	2800	2575	760	760	1014	298	15
295/75R22.5	16PR	146	143	M	9.00	8.25,9.00	3000	2725	830	830	1014	298	15
285/75R24.5	14PR	144	141	M	8.25	8.25	2800	2575	760	760	1050	283	15
285/75R24.5	16PR	147	144	M	8.25	8.25	3075	2800	830	830	1050	283	15
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1085	300	16

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	16PR	150	147	M	9.00	8.25,9.00	3350	3075	830	830	1085	300	21
12R22.5	18PR	152	149	L	9.00	8.25	3550	3250	930	930	1085	300	21
13R22.5	18PR	154	15	L	9.75	9.00	3750	3450	830	830	1124	320	21
295/80R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	900	900	1044	298	18.5
315/80R22.5	18PR	154	151	M	9.00	9.00,9.75	3750	3450	830	830	1076	312	21
315/80R22.5	18PR	154	151	K	9.00	9.00,9.75	3750	3450	830	830	1076	312	21
315/80R22.5	20PR	157	154	K	9.00	9.00,9.75	4125	3750	900	900	1076	312	21


FTG
 FUTURE TECHNOLOGY GENERATION


DD398




DD919

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	14PR	144	142	L	8.25	7.50,8.25	2800	2650	720	720	1065	279	23
11R22.5	16PR	146	143	L	8.25	7.50,8.25	3000	2725	830	830	1065	279	23
295/75R22.5	14PR	144	141	L	9.00	8.25,9.00	2800	2575	760	760	1020	298	23
295/75R22.5	16PR	146	143	L	9.00	8.25,9.00	3000	2725	830	830	1020	298	23
11R24.5	14PR	146	143	L	8.25	7.50,8.25	3000	2725	720	720	1116	279	23
11R24.5	16PR	149	146	L	8.25	7.50,8.25	3250	3000	830	830	1116	279	23
285/75R24.5	14PR	144	141	L	8.25	8.25	2800	2575	760	760	1056	283	23
285/75R24.5	16PR	147	144	L	8.25	8.25	3075	2800	830	830	1056	283	23

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	L	9.00	8.25,9.00	3550	3250	930	930	1085	300	23.5



FTG
FUTURE TECHNOLOGY GENERATION



Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION




DT966

Size	Ply Rating	Load Index Single	Dual	Speed Symbol	Standar Rim	Applicable Rim	Max Load(kg) Single	Dual	Pressure(kpa) Single	Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	14PR	144	142	M	8.25	7.50	2800	2650	720	720	1054	279	15.5
11R22.5	16PR	146	143	M	8.25	7.50	3000	2725	830	830	1054	279	15.5
11R22.5	16PR	148	145	M	8.25	7.50	3150	2900	850	850	1054	279	15.5
11R24.5	14PR	146	143	M	8.25	7.50,8.25	3000	2725	720	720	1104	279	15
11R24.5	16PR	149	146	M	8.25	7.50,8.25	3250	3000	830	830	1104	279	15
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1085	300	15
13R22.5	18PR	154	151	L	9.75	9.00	3750	3450	830	830	1124	320	15
255/70R22.5	16PR	140	137	M	7.50	7.50,8.25	2500	2300	830	830	930	255	13
275/70R22.5	16PR	148	145	M	8.25	7.50,8.25	3150	2900	900	900	958	276	14
285/75R24.5	14PR	144	141	M	8.25	8.25	2800	2575	760	760	1050	283	15
285/75R24.5	16PR	147	144	M	8.25	8.25	3075	2800	830	830	1050	283	15
295/60R22.5	16PR	144	141	M	9.00	8.25,9.00	2800	2575	830	830	926	292	15
295/60R22.5	18PR	150	147	M	9.00	9.00,9.75	3350	3075	900	900	926	292	15
295/75R22.5	14PR	144	141	M	9.00	8.25,9.00	2800	2575	760	760	1014	298	15
295/75R22.5	16PR	146	143	M	9.00	8.25,9.00	3000	2725	830	830	1014	298	15
295/80R22.5	16PR	150	147	M	9.00	8.25,9.00	3350	3075	830	830	1044	298	15
295/80R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	900	900	1044	298	15
315/60R22.5	18PR	152	148	M	9.75	9.00,9.75	3550	3150	900	900	950	313	15
315/70R22.5	18PR	154	150	M	9.00	9.00,9.75	3750	3350	900	900	1014	312	15
315/80R22.5	18PR	154	151	M	9.00	9.00,9.75	3750	3450	830	830	1076	312	15
315/80R22.5	20PR	157	154	M	9.00	9.00,9.75	4125	3750	900	900	1076	312	15

DD929

Size	Ply Rating	Load Index Single	Dual	Speed Symbol	Standar Rim	Applicable Rim	Max Load(kg) Single	Dual	Pressure(kpa) Single	Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	L	9.00	8.25,9.00	3550	3250	930	930	1085	300	23

FTG
FUTURE TECHNOLOGY GENERATION



DT966T

Size	Ply Rating	Load Index Single	Dual	Speed Symbol	Standar Rim	Applicable Rim	Max Load(kg) Single	Dual	Pressure(kpa) Single	Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	14PR	144	142	M	8.25	7.50	2800	2650	720	720	1054	279	10.5
11R22.5	16PR	146	143	M	8.25	7.50	3000	2725	830	830	1054	279	10.5
295/75R22.5	14PR	144	141	M	9.00	8.25,9.00	2800	2575	760	760	1014	298	10.5
295/75R22.5	16PR	146	143	M	9.00	8.25,9.00	3000	2725	830	830	1014	298	10.5



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DT969

DT977

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1085	300	15


Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1085	300	15



FTG
FUTURE TECHNOLOGY GENERATION

DT970

FTG
FUTURE TECHNOLOGY GENERATION



Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
385/65R22.5	20PR	164	---	K	11.75	12.25	5000	----	900	---	1072	389	16.7


Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1085	300	15
ST235/85R16	18PR	126	123	M	6 ^{1/2} J	6J,6 ^{1/2} J,7J,7 ^{1/2} J	1700	1550	760	760	806	235	9.5



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DA801

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
6.50R16LT	12PR	110	105	L	5.50F	5.00E,5.00F	1060	925	670	670	750	185	12
7.00R16LT	14PR	118	114	L	5.50F	6.00G	1320	1180	770	770	775	200	13
7.50R16LT	14PR	122	118	L	6.00G	5.50F,6.00G,6.50H	1500	1320	770	770	805	215	12.5
8.25R16LT	14PR	126	122	L	6.50H	6.00G,6.5	1700	1500	670	670	855	235	13
8.25R16LT	16PR	128	124	L	6.50H	6.00G,6.5	1800	1600	770	770	855	235	13
8.25R20	16PR	139	137	K	6.50	6.50T,7.0,7.00T	2430	2300	930	930	974	236	14
9.00R20	16PR	144	142	K	7.00	7.00T,7.50	2800	2650	900	900	1019	259	15
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	15
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	16
12.00R20	18PR	154	151	K	8.50	8.50V,9.00	3750	3450	830	830	1125	315	16.5
12.00R24	20PR	160	157	K	8.50	8.50V,9.00	4500	4125	900	900	1226	315	16
11R22.5	14PR	144	142	L	8.25	7.50,8.25	2800	2650	720	720	1054	279	16
11R22.5	16PR	146	143	L	8.25	7.50,8.25	3000	2725	830	830	1054	279	16
11R24.5	14PR	146	143	L	8.25	7.50,8.25	3000	2725	720	720	1104	279	16
11R24.5	16PR	149	146	L	8.25	7.50,8.25	3250	3000	830	830	1104	279	16
12R22.5	18PR	152	149	K	9.00	8.25,9.00	3550	3250	930	930	1085	300	17
315/80R22.5	20PR	157	154	K	9.00	9.00,9.75	4125	3750	900	900	1076	312	16.5



FTG
FUTURE TECHNOLOGY GENERATION



DA801+

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	16
12.00R20	18PR	154	151	K	8.50	8.50V,9.00	3750	3450	830	830	1125	315	16.5

DA802

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
6.50R16LT	12PR	110	105	L	5.50F	5.00E,5.00F	1060	925	670	670	750	185	10.5
7.00R16LT	14PR	118	114	L	5.50F	6.00G	1320	1180	770	770	775	200	11
7.50R16LT	14PR	122	118	L	6.00G	5.50F,6.00G,6.50H	1500	1320	770	770	805	215	12.5
ST235/85R16	14PR	126	123	L	6 1/2J	6J,6 1/2J,7J,7 1/2J	1700	1550	760	760	806	235	10.5
215/75R17.5	16PR	128	126	M	6.00	6.75	1800	1700	750	750	767	211	13
215/75R17.5	16PR	127	124	M	6.00	6.75	1750	1600	830	830	767	211	13
215/75R17.5	16PR	135	133	J	6.00	6.75	2180	2060	850	850	767	211	13
235/75R17.5	16PR	132	129	M	6.75	6.75,7.50	2000	1850	830	830	797	233	13
235/75R17.5	16PR	143	141	J	6.75	6.75,7.50	2725	2575	850	850	797	233	13
225/70R19.5	14PR	128	126	L	6.75	6.75,6.00	1800	1700	760	760	811	226	14
245/70R19.5	14PR	133	131	L	7.50	6.75,7.50	2060	1950	760	760	839	248	14
265/70R19.5	14PR	137	134	L	7.50	7.50,8.25	2300	2120	760	760	867	262	14
265/70R19.5	16PR	140	138	L	7.50	7.50,8.25	2500	2360	775	775	867	262	14
265/70R19.5	18PR	143	141	J	7.50	7.50,8.25	2725	2575	850	850	867	262	14
285/70R19.5	16PR	146	144	L	8.25	7.50,8.25,9.00	3000	2800	900	900	895	283	14
8R22.5	14PR	130	128	L	6.00	5.25,6.00,6.75	1900	1800	830	830	935	203	13
9R22.5	14PR	136	134	L	6.75	6.00,6.75,7.50	2240	2120	830	830	974	229	14
10R22.5	16PR	144	142	L	7.50	6.75,7.50	2800	2650	900	900	1020	254	14



DA802+

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
215/75R17.5	16PR	127	124	M	6.00	6.75	1750	1600	830	830	767	211	13
215/75R17.5	16PR	135	133	J	6.00	6.75	2180	2060	850	850	767	211	13





FTG
FUTURE TECHNOLOGY GENERATION



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DA803

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12.00R24	20PR	160	157	K	8.50	8.50V,9.0	4500	4125	900	900	1226	315	15

DA806

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
425/65R22.5	20PR	165	---	K	13.00	11.75,13.00	5100	---	825	---	1124	422	18



FTG
FUTURE TECHNOLOGY GENERATION

DA805

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
385/55R22.5	20PR	160	---	K	12.25	11.75,12.25	4500	---	900	---	996	386	15
385/65R22.5	20PR	160	---	L	11.75	12.25	4500	---	900	---	1072	389	16
425/65R22.5	20PR	164	---	K	12.25	11.75,13.00	5000	---	830	---	1124	422	16
425/65R22.5	20PR	164	---	K	13.00	11.75,13.00	5150	---	825	---	1124	422	16
445/65R22.5	20PR	169	---	K	13.00	13.00,14.00	5800	---	900	---	1150	444	15

FTG
FUTURE TECHNOLOGY GENERATION

DA808

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	K	9.00	8.25,9.00	3550	3250	930	930	1085	300	17



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DA818

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
6.50R16LT	12PR	110	105	L	5.50F	5.00E,5.00F	1060	925	670	670	750	185	10.5
7.00R16LT	14PR	118	114	L	5.50F	6.00G	1320	1180	770	770	775	200	11
7.50R16LT	14PR	122	118	L	6.00G	5.50F,6.50H	1500	1320	770	770	805	215	12.5
8.25R16LT	16PR	128	124	L	6.50H	6.00G,6.50	1800	1600	770	770	855	235	13
8.25R20	16PR	139	137	K	6.50	6.50T,7.0,7.00T	2430	2300	930	930	974	236	14
9.00R20	16PR	144	142	K	7.00	7.00T,7.50	2800	2650	900	900	1019	259	15
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	15
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	16
12.00R20	18PR	154	151	K	8.50	8.50V,9.00	3750	3450	930	930	1125	315	16.5
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	16.5
12.00R24	20PR	160	157	K	8.50	8.50V,9.00	4500	4125	900	900	1226	315	16.5
11R22.5	16PR	146	143	L	8.25	7.50,8.25	3000	2725	830	830	1054	279	16
12R22.5	18PR	152	149	K	9.00	8.25,9.00	3550	3250	930	930	1085	300	16
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1085	300	16
12R22.5	16PR	150	147	M	9.00	8.25,9.00	3350	3075	830	830	1085	300	16
13R22.5	18PR	158	156	K	9.75	9.00	4250	4000	900	900	1124	320	17
13R22.5	18PR	154	151	K	9.75	9.00	3750	3450	830	830	1124	320	17
315/80R22.5	18PR	154	151	K	9.00	9.00,9.75	3750	3450	830	830	1076	312	16
315/80R22.5	18PR	154	151	M	9.00	9.00,9.75	3750	3450	830	830	1076	312	16
315/80R22.5	20PR	157	154	K	9.00	9.00,9.75	4125	3750	900	900	1076	312	16



FTG
FUTURE TECHNOLOGY GENERATION



DA827

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	K	9.00	8.25,9.00	3550	3250	930	930	1085	300	16

DA818+

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	15
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	16
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	16.5

FTG
FUTURE TECHNOLOGY GENERATION



DA828

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12R22.5	18PR	152	149	K	9.00	8.25,9.00	3550	3250	930	930	1085	300	16



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DD308

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	14PR	144	142	M	8.25	7.50,8.25	2800	2650	720	720	1065	279	23
11R22.5	16PR	146	143	M	8.25	7.50,8.25	3000	2725	830	830	1065	279	23
11R24.5	14PR	146	143	M	8.25	7.50,8.25	3000	2725	720	720	1116	279	23
11R24.5	16PR	149	146	M	8.25	7.50,8.25	3250	3000	830	830	1116	279	23

DD319

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
8.25R20	14PR	136	134	K	6.50	6.50T,7.00,7.00T	2240	2120	830	830	974	236	15
8.25R20	16PR	139	137	K	6.50	6.50T,7.00,7.00T	2430	2300	930	930	974	236	15
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	18
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	18
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	18.5



FTG
FUTURE TECHNOLOGY GENERATION



DD318

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	18
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	18
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	18.5

FTG
FUTURE TECHNOLOGY GENERATION



DD328


Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standards Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
7.50R16LT	14PR	122	118	L	6.00G	5.50F,6.50H	1500	1320	770	770	805	215	15
8.25R16LT	16PR	128	124	L	6.50H	6.00G,6.50H	1800	1600	770	770	855	235	15
8.25R20	14PR	136	134	K	6.50	6.50T,7.00,7.00T	2240	2120	830	830	974	236	15
8.25R20	16PR	139	137	K	6.50	6.50T,7.00,7.00T	2430	2300	930	930	974	236	15
9.00R20	16PR	144	142	K	7.00	7.00T,7.50	2800	2650	900	900	1019	259	16
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	17
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	18.5
12.00R20	18PR	154	151	K	8.50	8.50V,9.00	3750	3450	830	830	1125	315	19
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	19



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DD328+

DD335

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	18.5
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	19

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	16PR	146	143	M	8.25	7.50,8.25	3000	2725	830	830	1065	279	18
12R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	930	930	1096	300	19
13R22.5	18PR	154	151	L	9.75	9.00	3750	3450	830	830	1136	320	20
225/70R19.5	14PR	128	126	M	6.75	6.00,6.75	1800	1700	760	760	817	226	15
245/70R19.5	16PR	136	134	L	7.50	6.75,7.50	2240	2120	825	825	839	248	15
265/70R19.5	16PR	140	138	M	7.50	6.75,7.50,8.25	2500	2360	775	775	867	262	15.5
265/70R19.5	18PR	143	141	J	7.50	6.75,7.50,8.25	2725	2575	850	850	867	262	15.5
275/70R22.5	16PR	148	145	M	8.25	7.50,8.25	3150	2900	900	900	958	276	18.5
285/70R19.5	16PR	146	144	M	8.25	7.50,8.25,9.00	3000	2800	900	900	895	283	16.5
285/70R19.5	18PR	150	148	J	8.25	7.50,8.25,9.00	3350	3150	900	900	895	283	16.5
295/60R22.5	16PR	144	141	L	9.00	8.25,9.00	2800	2575	830	830	926	292	20
295/60R22.5	18PR	150	147	L	9.00	8.25,9.00	3350	3075	900	900	926	292	20
295/80R22.5	16PR	150	147	M	9.00	8.25,9.00	3350	3075	830	830	1050	298	19
295/80R22.5	18PR	152	149	M	9.00	8.25,9.00	3550	3250	900	900	1050	298	19
315/60R22.5	18PR	152	148	M	9.75	9.00,9.75	3550	3150	900	900	950	313	18
315/70R22.5	18PR	154	150	M	9.00	9.00,9.75	3750	3350	900	900	1014	312	19
315/80R22.5	20PR	157	154	M	9.00	9.00,9.75	4125	3750	900	900	1082	312	19



FTG
FUTURE TECHNOLOGY GENERATION



DD329

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standart Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	18.5
11.00R20	18PR	152	149	K	8.00	8.00V,8.50	3550	3250	930	930	1085	293	20
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1125	315	20.5



FTG
FUTURE TECHNOLOGY GENERATION

Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DD905

DD907

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
10.00R20	18PR	149	146	K	7.50	7.50V,8.00	3250	3000	930	930	1054	278	18
13R22.5	18PR	154	151	L	9.75	9.00	3750	3450	830	830	1136	320	21
13R22.5	18PR	154	151	K	9.75	9.00	3750	3450	830	830	1136	320	21
315/80R22.5	18PR	156	150	K	9.00	9.00,9.75	4000	3350	850	850	1082	312	21
315/80R22.5	20PR	157	154	L	9.00	9.00,9.75	4125	3750	900	900	1082	312	21

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12.00R24	20PR	160	157	K	8.50	8.50V,9.00	4500	4125	900	900	1226	315	19



FTG
FUTURE TECHNOLOGY GENERATION

DD906



Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	16PR	148	145	L	8.25	7.50,8.25	3150	2900	850	850	1054	279	21
12R22.5	18PR	152	149	L	9.00	8.25,9.00	3550	3250	930	930	1085	300	21
295/80R22.5	18PR	152	149	L	9.00	8.25,9.00	3550	3250	900	900	1044	298	21


FTG
 FUTURE TECHNOLOGY GENERATION


Tire Direct

La nueva generación
FTG
 FUTURE TECHNOLOGY GENERATION


DD717

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	16PR	148	145	G	8.25	7.50,8.25	3150	2900	850	850	1065	279	23
12R22.5	18PR	152	149	G	9.00	8.25,9.00	3550	3250	930	930	1096	300	23

DD767

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
8.25R16LT	16PR	128	124	F	6.50H	6.00G,6.50	1800	1600	770	770	865	235	17
8.25R20	16PR	139	137	F	6.50	6.50T,7.00,7.00T	2430	2300	930	930	986	236	19
9.00R20	16PR	144	142	F	7.00	7.00T,7.50	2800	2650	900	900	1030	259	20
10.00R20	18PR	149	146	F	7.50	7.50V,8.00	3250	3000	930	930	1065	278	22
11.00R20	18PR	152	149	D	8.00	8.00V,8.50	3550	3250	930	930	1096	293	22
12.00R20	20PR	156	153	D	8.50	8.50V,9.00	4000	3650	900	900	1136	315	22.5


FTG
 FUTURE TECHNOLOGY GENERATION


DD727

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11.00R20	18PR	152	149	D	8.00	8.00V,8.50	3550	3250	930	930	1096	293	24
12.00R20	20PR	156	153	D	8.50	8.50V,9.00	4000	3650	900	900	1136	315	24.5

FTG
 FUTURE TECHNOLOGY GENERATION


DD777

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
7.50R16LT	14PR	122	118	F	6.00G	5.50F,6.50H	1500	1320	770	770	815	215	16.5
8.25R16LT	16PR	128	124	F	6.50H	6.00G,6.50	1800	1600	770	770	865	235	17.5
8.25R20	14PR	136	134	F	6.50	6.50T,7.00,7.00T	2240	2120	830	830	986	236	17.5
8.25R20	16PR	139	137	F	6.50	6.50T,7.00,7.00T	2430	2300	930	930	986	236	17.5
11.00R20	18PR	152	149	D	8.00	8.00V,8.50	3550	3250	930	930	1096	293	24
12.00R20	18PR	154	151	F	8.50	8.50V,9.00	3750	3450	830	830	1136	315	24.5
12.00R20	20PR	156	153	D	8.50	8.50V,9.00	4000	3650	900	900	1136	315	24.5
295/80R22.5	18PR	152	149	K	9.00	8.25,9.00	3550	3250	900	900	1050	298	19



FTG
FUTURE TECHNOLOGY GENERATION



Tire Direct
La nueva generación

FTG
FUTURE TECHNOLOGY GENERATION



DD777+

DD378S

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12.00R20	20PR	156	153	D	8.50	8.50V,9.00	4000	3650	900	900	1136	315	24.5

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
11R22.5	16PR	146	143	M	8.25	7.50,8.25	3000	2725	830	830	1065	279	21



FTG
FUTURE TECHNOLOGY GENERATION



DD787

FTG
FUTURE TECHNOLOGY GENERATION



DD379S

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
12.00R20	20PR	156	153	K	8.50	8.50V,9.00	4000	3650	900	900	1136	315	22

Size	Ply Rating	Load Index Single	Load Index Dual	Speed Symbol	Standed Rim	Applicable Rim	Max Load(kg) Single	Max Load(kg) Dual	Pressure(kpa) Single	Pressure(kpa) Dual	Overall DIM(mm)	Section Width(mm)	Tread Depth(mm)
315/80R22.5	18PR	154	151	M	9.00	9.00,9.75	3750	3450	830	830	1082	312	24